

2. Lord Fabrik recommends that installers use a hard, acrylic, pigmented, wall-protecting primer that is SPECIFICALLY made for WALLCOVERING INSTALLATION and WALL PROTECTION. **DO NOT USE R-35.**
3. Allow the primer to dry thoroughly before hanging.



INSTALLATION ADHESIVE

1. We recommend **Roman 555** a clear, pre-mixed, low-moisture vinyl-over-vinyl adhesive for permanent installations. The **Roman 555** is key as other adhesives may leave bubbles.
2. Apply the paste to the back of the wallcovering, which will become flexible and easy to hang.
3. **Book the wall covering and let it lay for a period of 25-30 minutes.** This allows the fabric, made from natural cotton, to shrink prior to installation. You can book multiple units of wall covering at a time.

TRIMMING

1. The edges have been pre-trimmed at the factory and the installation is made with a double-cut. Change your blades often.
2. After installing two bolts, take a few minutes to shade the strips from light to dark to insure the most even shading. The installer may reverse strips if he feels that it will produce the most even shading. Once you are satisfied with the shading from the first two bolts, install the balance of the rolls.
3. A double-cut is essential on this organic, natural-fiber wallcovering to create as fine a seam as possible.

TIPS

1. Apply pressure on the wallcovering to ensure proper adhesion with a smoothing tool.
2. DO NOT allow paste or excessive water to stain the front of the wallcovering. Both paste and excessive water will change the color of the natural canvas on the face.
3. Paste may be applied on several units prior to installation for booking time.
4. Consider using a light painters tape to cover the edges of previously installed strips, so that the paste coming out from the seams will not settle on the installed strips.
5. Gently smooth the wallcovering using a plastic smoother. Use a seam roller on the edges or for any creases.
6. These wallcoverings may be cleaned using a damp cloth or vacuum with a soft brush attachment.

Contact us at (301) 798-4888 for any questions with regards to installation of the Lord Fabrik Canvas Peace Collection.